

URINALS

Siphonic urinal TAMARO 84009.0



TECHNICAL DATA

Order no.	84009.0
Certified to	EN 80, EN 13407
matching for	LIS CU1 Concealed frame for urinal without integrated control, order no. 89266.3 LIS SMART CONTROL-U, order no. 37066.0
Water inlet	concealed
Outlet	horizontal or vertical
Flushing quantity	minimum 1 l
Flushing capacity	minimum 0.3 l/s
Weight	21,5 kg
Mounting acc. excl.	LIS CU1 and SMART CONTROL-U horizontal inlet connection 1/2", order no. 89900.5 all siphons has to be used in combination with the outlet connection pipe (order no. 89397.3) 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), order no. 89418.1 1-litre siphon with horizontal and vertical outlet DN 50 SH 50 (standard Europe, except CH and UK), order no. 89583.9

Mounting acc. excl.	1-litre siphon with horizontal and vertical outlet DN 40 SH 50 (standard CH), order no. 89584.0 Stone screws, order no. 89406.0
---------------------	--

Colours see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-TAMARO, sanitary ceramic EN 80, EN 13407, dimensions 395 x 360 x 770 mm minimum 1-l flush, water inlet concealed, outlet horizontal or vertical, flushing rate minimum 0.3 l/s
Special feature: Vacuum and performance tested
Further options / accessories: LIS horizontal inlet connection, 1-litre siphon with horizontal outlet DN 50 (standard Europe, except CH and UK), 1-litre siphon with horizontal and vertical outlet DN 50 SH 50 (standard Europe, except CH and UK) and outlet DN 40 SH 50 (standard CH), LIS CU1 concealed frame for urinal without integrated control or LIS SMART CONTROL-U concealed kit for urinal flash control and front plate with infrared sensor
Order no. 84009.0

TECHNICAL DRAWINGS / S 1 : 20

