

INEO INSTALLATION SYSTEM

Installation element with cistern for wallhung WC and for shower toilet

INEOLINK H926103



TECHNICAL DATA

Order no.	H926103	Water temperature	max. 25°C
Certified to	EN 14055, EN 1519	Tank	Installation depth: 120 mm, material PP
matching for	Shower toilet	Installation depth	125 mm
Specifications	U-shaped support frame, for installation in front of a solid wall or in drywall constructions. Construction height 1090 mm. With front operated. Cistern pre-assembled, Dual-Flush 6/3-l (4/3-l-flush), with water condensation insulation. Supporting "U-shaped" with fixing points adjustable to the wall. Capable to resist 400 kg	Weight	8,0 kg
Water inlet	rear R 1/2, brass, matching for standard pipe systems	Mounting acc. incl.	Angle valve 1/2", protection box for service opening, protection set with cover, fastening material and 2x M12 threaded rods, Conduit pipe for feed pipe of shower toilet, WC connection set DN 90, Drain elbow DN 90, HDPE with adapter DN 90/110, HDPE.
Outlet	DN 90/110, pipe clamp with depth adjustable, sound decoupled	Accessories excl.	Flush plates dual flush with front actuation
Flow pressure range	0.5-10 bar	Mounting information	Height from finished floor to top of WC pre-set to 400 mm.

TECHNICAL DRAWINGS / S 1 : 20

